



## the complete fire protection solution

Water / Dry Powder / Carbon Dioxide / Foam Fire Extinguishers

Fire Blankets / Trolley units

# Water

Water Fire Extinguishers are ideal for extinguishing Class A Fires. The TITAN 9ltr Water Fire Extinguisher is perfect for use in a range of applications including offices and warehouses and the extinguishant is just pure water making the fire extinguishers extremely environmentally friendly and quick and simple to discharge test.

- > BS EN 3 Kitemarked
- > CE Marked
- > Plastic base for added protection
- > Easy to read pressure gauge
- > High quality corrosion resistant finish
- > Supplied complete with wall mounting bracket
- > Polyethylene internal lining
- > Full range of spare parts available
- > 5 year warranty



Technical specification:	TITANPSE05-01
Capacity	9 litres
Fire rating	13A
Extinguishing medium	Water
Operating temperature	+5°C to +60°C
Cylinder height and diameter	625mm/190mm
Cylinder material	Steel
Pressurising gas	Nitrogen

# Foam

Our comprehensive range of Foam Fire Extinguishers includes four models: 1ltr, 2ltr, 6ltr and 9ltr ensuring that TITAN fire extinguishers offer a great range of protection for Class A and B Fires. Foam fire extinguishers are a popular choice for use in offices and industrial setting such as warehouses. The 1ltr and 2ltr models are supplied complete with transport bracket.

- > BS EN 3 Kitemarked (6ltr and 9ltr Foam Fire Extinguishers only)
- > CE Marked
- > Plastic base for added protection (not 1ltr and 2ltr models)
- > Easy to read pressure gauge
- > High quality corrosion resistant finish
- > Supplied complete with wall mounting bracket
- > Polyethylene internal lining
- > Full range of spare parts available
- > 5 year warranty



Technical specification:	TITANPSE06-00	TITANPSE06-01	TITANPSE06-02	TITANPSE06-03
Capacity	1 litre	2 litres	6 litres	9 litres
Fire rating	5A 21B	8A 34B	13A 144B	21A 183B
Extinguishing medium	Foam	Foam	Foam	Foam
Operating temperature	0°C to 60°C	0°C to 60°C	0°C to 60°C	0°C to 60°C
Cylinder height	333mm	378mm	550mm	625mm
Cylinder diameter	85mm	110mm	165mm	190mm
Cylinder material	Steel	Steel	Steel	Steel
Pressurising gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen

# Dry Powder

Dry Powder Fire Extinguishers are excellent multi-purpose fire extinguishers offering protection against class ABC fires. The comprehensive TITAN range offers a range of model sizes including 1, 2, 3, 6 and 9kg making the fire extinguishers ideal for a range of applications including use in vehicles. The 1kg, 2kg and 3kg models are supplied complete with transport brackets.

- > BS EN 3 Kitemarked (not 3kg model)
- > CE Marked
- > 6kg and 9kg models supplied with plastic base for added protection
- > Easy to read pressure gauge
- > High quality corrosion resistant finish
- > 6kg and 9kg models are supplied complete with wall mounting bracket
- > Full range of spare parts available
- > 5 year warranty
- > 1kg, 2kg and 3kg models supplied with study transport bracket



Technical specification:	TITAN PSE03-01	TITAN PSE03-02	TITAN PSE03-05	TITAN PSE03-03	TITAN PSE03-04
Capacity	1kg	2kg	3kg	6kg	9kg
Fire rating	5A 34B/C	13A 70B/C	13A 89B/C	27A 144BC	34A 233B/C
Extinguishing medium	Dry Powder	Dry Powder	Dry Powder	Dry Powder	Dry Powder
Operating temperature	-30°C to 60°C	-30°C to 60°C	-30°C to 60°C	-30°C to 60°C	-30°C to 60°C
Cylinder height	333mm	380mm	421mm	550mm	595mm
Cylinder diameter	85mm	110mm	120mm	158mm	190mm
Cylinder material	Steel	Steel	Steel	Steel	Steel
Pressurising gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen

# Carbon Dioxide

Carbon Dioxide fire extinguishers are ideal for use on Class B electrical and liquid fires. Carbon Dioxide fire extinguishers can be used to combat fires involving live electrical equipment making them perfect for use in a wide range of environments including offices, warehouses and industrial settings. TITAN branded refurbished carbon dioxide fire extinguishers are also available.

- > BS EN 3 Kitemarked
- > CE Marked
- > 2kg fire extinguisher is supplied with frost free horn and the 5kg fire extinguisher is supplied complete with hose and horn
- > High quality corrosion resistant finish
- > Supplied complete with wall mounting bracket
- > Full range of spare parts available
- > 5 year warranty



Technical specification:	TITANCO2	TITANCO2-5KG
Capacity	2kg	5kg
Fire rating	34B	55B
Extinguishing medium	Carbon Dioxide	Carbon Dioxide
Operating temperature	-20°C to 60°C	-20°C to 60°C
Cylinder height	495mm	673mm
Cylinder diameter	117mm	153mm
Cylinder material	Aluminium	Aluminium

# Fire blankets

The TITAN range also includes a comprehensive range of four Kitemarked fire blankets that represent the highest quality as well as offering exceptional value for money. The fire blankets are a slim-line design with a wipe clean, rigid plastic case that can be quickly wall mounted and offers easy access to the fire blanket inside.

- > Range of four different sizes available
- > Manufactured to BS EN 1869:1997 and BSI Kitemarked
- > Slim-line design
- > Wipe clean, rigid plastic case
- > Case includes holes for wall mounting
- > Easy to inspect
- > Hinged base ensuring ease of access
- > 12 month warranty



TITANFB002	1 metre x 1 metre
TITANFB004	1.2 metre x 1.2 metre
TITANFB005	1.8 metre x 1.2 metre
TITANFB006	1.8 metre x 1.8 metre

# Trolley Units

TITAN Stored pressure fire extinguisher wheeled trolley units are available in ABC Dry Powder and AFFF Foam versions and offer exceptional value for money as well as the high quality that you would expect from TITAN fire fighting products. TITAN trolley units are ideal for use in a wide range of commercial and industrial settings.

- > CE Marked
- > Wheeled trolley units are ideal for fighting larger fires
- > Wheeled trolley units include sturdy wheels and handles for ease of movement
- > Can be used and operated by one person
- > Stored Pressure
- > Supplied filled and ready for use
- > Manufactured from robust materials



	PSE27-01 25ltr Foam	PSE27-02 50ltr Foam	PSE24-01 25kg Dry Powder	PSe24-02 50kg Dry Powder
Volume (litres)	30	59	30	59
Filled weight (kg)	55	95	55	95
Temperature range	0°C—55°C	0°C—55°C	-20°C—55°C	-20°C—55°C
Working pressure (Bar)	15	15	15	15
Test pressure (Bar)	35	35	35	35
Outer diameter (mm)	270	320	270	320
Minimum wall thickness (mm)	2.50	3.00	2.50	3.00
Packing size (mm)	580 x 470 x 970	630 x 500 x 1110	580 x 470 x 970	630 x 500 x 1110

The TITAN fire extinguisher range consists of a wide selection of carbon dioxide, foam, water and powder fire extinguishers offering impressive fire ratings, as well as excellent value for money without compromising on quality. All fire extinguishers are Kitemarked (exceptions apply) and CE Marked. TITAN branded fire blankets, photo luminescent signs and fire extinguisher trolley units are also available making TITAN the complete fire protection solution.

Express Fire Equipment Ltd  
Units 3-4 Mersey Road Industrial Estate  
Mersey Road North  
Failsworth  
Manchester  
M35 9LU

T: +44 (0)161 688 5050

F: +44 (0)161 688 5151

E: [info@expressfire.com](mailto:info@expressfire.com)

URL: [www.expressfire.com](http://www.expressfire.com)