






Foam

Foam extinguishers are available in 6ltr and 9ltr standard versions or 6ltr anti-freeze stored pressure versions as well as 6ltr eco foam and 6ltr foam polar liquids cartridge operated versions. The extinguishers come with a five year guarantee provided they are serviced and maintained annually by a competent person in accordance with BS5306 Pt3, using manufacturer's spare parts, and in lien with the manufacturer's recommendations. Foam fire extinguishers are suitable for Class A and B fires involving flammable liquids such as oils, spirits, greases, fats and certain plastics. All of our water based extinguishers are safe for inadvertent use on electrical equipment up to 1,000v at a distance of 1 metre.

Class A: Carbonaceous material such as wood, paper and textile

Class B: Flammable liquids such as petrol, oil, fats, solvents and paints

	S6DN	S9DN	S6DF	S6AKP	S6AKA
					
Model type	6ltr Foam Stored Pressure	9ltr Foam Stored Pressure	9ltr Foam Anti-freeze Stored Pressure	6ltr Eco Foam Cartridge Operated	6ltr Foam Polar Cartridge Operated
Body material	Steel cylinder, plastic boot	Steel cylinder, plastic boot	Steel cylinder, plastic boot	Steel cylinder, plastic boot	Steel cylinder, plastic boot
Neck ring material	Steel	Steel	Steel	Steel	Steel
Valve	Brass	Brass	Brass	Brass / Plastic spindle	Brass / Plastic spindle
Hose/Nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle	Rubber hose with brass thread ring/ Special nozzle
Internal finish	Polyester powder coating	Polyester powder coating	Polyester powder coating	Polyester powder coating	Polyester powder coating
External finish	Polyester powder coating	Polyester powder coating	Polyester powder coating	Polyester powder coating	Polyester powder coating
Charge (Ltr)	6	9	6	6	6
Extinguishant	AFFF	AFFF	AFFF, Anti-freeze	AFFF Cartridge	Special solution Cartridge
Fire rating	13A / 183B	21A / 233B	13A / 144B	21A / 183B	13A / 113B 55B Polar Liquids
Working pressure @ 20°C	15 bar	15 bar	15 bar	15 bar	15 bar
Test pressure	30 bar	30 bar	30 bar	30 bar	30 bar
Operating temperature	5°C to 60°C	5°C to 60°C	-20°C to 60°C	-20°C to 60°C	5°C to 60°C
Full weight (kg)	10.00kg	14.80kg	11.00kg	11.00kg	11.00kg
Empty weight (kg)	4	5,8			
Overall width (mm)	225mm	240mm	225mm	260mm	260mm
Overall height (mm)	565mm	535mm	565mm	580mm	580mm
Cylinder diameter (mm)	150	190	150	150	150
Min. Discharge range (m)	4-6	4-6	4-6	4-6	4-6
Discharge (s)	24	31	24	22	22
Mounting bracket	Rubber padded wall bracket	Rubber padded wall bracket	Rubber padded wall bracket	Rubber padded wall bracket	Rubber padded wall bracket
Carton Size (mm)	200x155x590	240x193x565	200x155x590	200x155x590	200x155x590
Kitemark approval	Y	Y	Y	Y	N
CE marked	Y	Y	Y	Y	Y
Marine approved	Y	Y	N	N	N
BAFE approved	Y	Y	Y	Y	N