



Sicherheit und Feuerschutz

PG12 Tandem 12kg Powder Fire Extinguisher



Application and use:

The Tandem 12kg Powder fire extinguisher can be operated as a standard portable fire extinguisher but can also be wall mounted to operate as an automatic fire extinguisher. To use for automatic operation, the extinguisher will protect all objects or areas covered by the direct agent flow. The fire extinguisher offers protection against Class A and B fires and class C fires when used as a hand-held portable. Typical applications include workshops, industrial plants, shops, offices, garages, petrol stations, portakabins, heating systems, small storage areas and farm enterprises.

Key product features :

- ✓ Safe for use on electrical equipment
- ✓ Temperature range of -20°C to 60 °C
- ✓ Delivery of extinguishant is trigger controlled for use as a portable fire extinguisher, all contents will be discharged when used as an automatic extinguisher
- ✓ Pressure gauge with permanent pressure control
- ✓ Test valve so that the pressure can be independently verified
- ✓ High corrosion protection for the entire unit, inside and out
- ✓ Special sprinkler (68°C) for sensing fires
- ✓ Steel cylinder finished in high quality polyester powder coating, free of Cadmium and Triglycid Isocyanurate
- ✓ Rubber padded wall bracket protects cylinder coating

Approvals:

- ✓ European Standard EN3
- ✓ Cylinder and entire extinguisher tested to European Pressure Equipment Directive (PED)
- ✓ CE mark according to PED 97/23/EG
- ✓ Proven in specialist applications
- ✓ Cylinder 100% pressure tested
- ✓ Extinguisher, valve and hose corrosion tested (ISO 3768)
- ✓ Manufacturer is ISO 9001 : 2000 certified by TUV CERT
- ✓ Suppression agent tested and certified by European toxicological and hygiene safety Notified Body

Technical specification:

Capacity	Cylinder	Type	Temp. Range	Rating	Weight	Width	Height
12kg	Steel	Stored Pressure	-20°C to 60°C	55A/ 233B/C	19.00kg	250mm	670mm

