

PG2PMK 2kg Dry Powder Stored Pressure Fire Extinguisher



Application and use:

Designed to combat A, B and C fires, the TOTAL 2kg dry powder fire extinguisher is suited for areas of mixed risk. These units are particularly suited to flammable liquid fires as well as flammable gas fires such as methane, propane, hydrogen and natural gas. The 2kg version comes complete with vehicle bracket and is particularly suited for use in the home.

Key product features:

- ✓ Safe for use on electrical equipment
- ✓ Pressure gauge for permanent pressure control
- ✓ Squeeze grip control allows total control of discharge
- ✓ Test valve located behind the pressure gauge ensuring a leak free seal and ease of maintenance
- ✓ Full range of TOTAL spares available
- ✓ Specialised production technology for powder extinguishant – high flow and moisture resistant.
- ✓ Steel cylinder finished in high quality polyester powder coating free of Cadmium and Triglycid Isocyanurate

Approvals:

- ✓ Approved to BS EN 3 (Kitemark)
- ✓ CE marked scoring to PED 97/23/EG
- ✓ Manufacturer is ISO 9001 : 2000 certified by Tuv CERT
- ✓ Cylinder and entire extinguisher tested to European Pressure Equipment Directive (PED)
- ✓ Cylinder 100% pressure tested
- ✓ Extinguisher, valve and hose corrosion tested to ISO 3768
- ✓ Certified according to Marine Equipment Directive (MED) 96/98/EG Ⓢ

Technical specification:

Capacity	Cylinder	Type	Temp. Range	Rating	Weight	Width	Height	Agent
2kg	Steel	Stored Pressure	-20°C to 60°C	13A 89B/C	3.70kg	120mm	355mm	Dry Powder

