

PG6Hi-BK Powder - Coal Dust Fire Extinguisher



Application and use:

The 6kg powder coal dust fire extinguisher has been particularly designed to combat coal dust fires but the extinguisher will also combat other dust fire risks. The extinguisher can also be used as a standard extinguisher to combat A, B and C class fires once the applicator has been removed.

Key product features :

- ✓ Safe for use on electrical equipment
- ✓ Temperature range of -20°C to 60 °C
- ✓ Squeeze grip control valve allows total control of the discharge
- ✓ Special powder applicator reduces the risk of explosion
- ✓ Steel cylinder finished in high quality polyester powder coating, free of Cadmium and Triglycid Isocyanurate
- ✓ Rubber padded wall bracket protects cylinder coating

Approvals:

- ✓ European Standard EN3
- ✓ Cylinder and entire extinguisher tested to European Pressure Equipment Directive (PED)
- ✓ CE mark according to PED 97/23/EG
- ✓ Cylinder 100% pressure tested
- ✓ Extinguisher, valve and hose corrosion tested (ISO 3768)
- ✓ Suppression agent tested and certified by European toxicological and hygiene safety Notified Body
- ✓ Manufacturer is ISO 9001 : 2000 certified by TUV CERT

Technical specification:

| Capacity | Cylinder | Type | Temp. Range | Rating | Weight | Width | Height |
|----------|----------|-----------------|---------------|---------------|---------|-------|--------|
| 6kg | Steel | Stored Pressure | -20°C to 60°C | 43A 233B/C | 10.50kg | 225mm | 560mm |

