



Sicherheit und Feuerschutz

## PG9PDY 9kg Dry Powder Stored Pressure Fire Extinguisher



### Application and use:

Designed to combat A, B and C fires, the TOTAL 9kg dry powder fire extinguisher is suitable for use in areas of mixed risk. These units are particularly suited to flammable liquid fires as well as flammable gas fires such as methane, propane, hydrogen and natural gas. The 9kg version comes complete with a sturdy bracket for wall mounting.

### Key product features:

- ✓ Safe for use on electrical equipment
- ✓ Pressure gauge for permanent pressure control
- ✓ Squeeze grip control allows total control of discharge
- ✓ Test valve located behind the pressure gauge ensuring a leak free seal and ease of maintenance
- ✓ Full range of TOTAL spares available
- ✓ Specialised production technology for powder extinguishant – high flow and moisture resistant.
- ✓ Rubber padded wall bracket protects the coating
- ✓ Steel cylinder finished in high quality polyester powder coating free of Cadmium and Triglycid Isocyanurate

### Approvals:

- ✓ Approved to BS EN 3 (Kitemark)
- ✓ CE marked scoring to PED 97/23/EG
- ✓ Manufacturer is ISO 9001 : 2000 certified by Tuv CERT
- ✓ Cylinder and entire extinguisher tested to European Pressure Equipment Directive (PED)
- ✓ Cylinder 100% pressure tested
- ✓ Extinguisher, valve and hose corrosion tested to ISO 3768
- ✓ Certified according to Marine Equipment Directive (MED) 96/98/EG Ⓢ

### Technical specification:

Capacity	Cylinder	Type	Temp. Range	Rating	Weight	Width	Height	Agent
9kg	Steel	Stored Pressure	-20°C to 60°C	43A 233B/C	15.00kg	250mm	505mm	Dry Powder

