

TOTAL

Sicherheit und Feuerschutz

S6DF 6ltr Foam Anti-Freeze Stored Pressure Fire Extinguisher



Application and use:

The TOTAL 6ltr foam anti-freeze fire extinguisher offers all of the benefits of the standard 6ltr foam with the added benefit of use in areas where temperatures as low as -20°C may be experienced. Typical uses include garages, workshops, office stores, railway stations and wagons. The foam 6ltr anti-freeze is suitable for use against class A and B fires.

Key product features:

- ✓ Swirl-effect, multi-spray nozzle for optimal droplet dimension and projection range
- ✓ Anti-freeze protection down to -20°C
- ✓ Internal corrosion protected with 1mm coating
- ✓ Squeeze grip control valve allows total control of discharge
- ✓ Safe for inadvertent use on electrical equipment (up to 1000v at 1m distance)
- ✓ Pressure gauge with permanent pressure control
- ✓ A test valve is located behind the pressure gauge, ensuring a leak free seal and ease of maintenance
- ✓ Large diameter neck ring for easier service inspection
- ✓ High corrosion protection for entire unit, inside and out
- ✓ Cadmium and TGIC-free polyester powder coating
- ✓ Rubber padded wall bracket protects the coating
- ✓ Container with external thread for protection of the anti-corrosive coating, even in the threaded area
- ✓ Added purification tablet means no contamination issues

Approvals:

- ✓ Approved to BS EN 3 (Kitemark)
- ✓ CE marked according to PED 97/23/EG
- ✓ Manufacturer is ISO 9001 : 2000 certified by Tuv CERT
- ✓ Cylinder and entire extinguisher tested to European Pressure Equipment Directive (PED)
- ✓ Cylinder 100% pressure tested
- ✓ Extinguisher, valve and hose corrosion tested to ISO 3768
- ✓ Each cylinder is inspected using high-voltage test equipment at the initial coating stage and at the final production process
- ✓ Suppression agent tested and certified by European toxicological and hygiene safety Notified Body

Technical specification:

Capacity	Cylinder	Type	Temp. Range	Rating	Weight	Width	Height
6ltr	Steel	Stored Pressure	-20°C to 60°C	13A/144B	11.00kg	225mm	565mm

