


Tandem Powder & Foam

The Tandem dual purpose fire extinguishers are available in 9ltr Foam or 6kg or 12kg Dry Powder versions. The extinguishers come with a five year guarantee provided they are serviced and maintained annually by a competent person in accordance with BS5306 Pt3, using manufacturer's spare parts, and in line with the manufacturer's recommendations.

The tandem extinguishers can be used as a standard fire extinguisher or can be wall-mounted inside premises to ensure protection during periods of non-occupancy. Typical applications include industrial plants, shops., offices, heating systems, portakabins and petrol stations. The Foam extinguishers are suitable for use on Class A and B fires and the Dry Powder extinguishers can be used on class A, B and C fires. The Foam extinguishers are safe for inadvertent use on electrical equipment up to 1,000v at a distance of 1 metre.

	S9Tandem	PG6 Tandem	PG12 Tandem
			
Model type	9ltr Foam Tandem Stored Pressure	6kg Tandem Stored Pressure	12kg Tandem Stored Pressure
Body material	Steel cylinder, plastic boot	Steel cylinder, plastic boot	Steel cylinder, plastic boot
Neck ring material	steel	steel	steel
Valve	Brass	Brass	Brass
Hose/Nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle
Internal finish	Polyester powder coating	N/A	N/A
External finish	Polyester powder coating	Polyester powder coating	Polyester powder coating

	S9 Tandem	PG6 Tandem	PG12 Tandem
Charge (Ltr/Kg)	9	6	12
Extinguishant	AFFF	ABC Dry Powder Neutrex 70	ABC Dry Powder Neutrex 70
Fire rating	21A / 233B (when used as portable)	34A / 233B/ C as portable extinguisher	55A / 233B/ C as portable exting- guisher
Working pressure @ 20°C	15	15	15
Test pressure	30	29	30
Operating temperature	0°C to 60°C	-20°C to 60°C	-20°C to 60°C
Full weight (kg)	16.0kg	11.0kg	19.00kg
Empty weight (kg)	7	5	7
Overall width (mm)	250mm	230mm	250mm
Overall height (mm)	650mm	600mm	670mm
Cylinder diameter (mm)	180	150	190
Min. Discharge range (m)	4-6m, depending upon installation height	4-6m, depending upon installation height	4-6m, depending upon installation height
Discharge (s)	32	15	23
Mounting bracket	Rubber padded wall bracket	Rubber padded wall bracket	Rubber padded wall bracket
Carton Size (mm)	208x193x725	200x155x590	208x193x725
Kitemark approval	N	N	N
CE marked	Y	Y	Y
Marine approved	N	N	N
BAFE approved	N	N	N