



# Water: Saw dust

The 6 and 9litre water saw dust fire extinguishers are specifically designed for use against the smouldering fires of saw dust with the main applications being carpentry, chipboard manufacturing and working. The extinguishers also offer protection against Class A fires.

The extinguishers come with a five year guarantee provided they are serviced and maintained annually by a competent person in accordance with BS5306 Pt3, using manufacturer's spare parts, and in line with the manufacturer's recommendations.

	WG6 H	WG9 H
		
Model type	Stored Pressure	Stored Pressure
Body material	Steel cylinder, plastic boot	Steel cylinder
Neck ring material	Steel	Steel
Valve	Knock down button	Knock down button
Hose	Rubber hose with brass thread ring	Rubber hose with brass thread ring
Internal finish	Polyester powder coating	Polyester powder coating
External finish	Polyester powder coating	Polyester powder coating

	WG6 H	WG9 H
Charge (Ltr)	6	9
Extinguishant	Water	Water
Fire rating	13A	21A
Working pressure @ 20°C	15 bar	15 bar
Test pressure	30 bar	30 bar
Operating temperature	5°C to 60°C	5°C to 60°C
Full weight (kg)	11.00kg	15.00kg
Empty weight (kg)	5	6
Overall width (mm)	230mm	230mm
Overall height (mm)	555mm	635mm
Cylinder diameter (mm)	150	190
Min. Discharge range (m)	Special nozzle to be used just over wood flour fire	Special nozzle to be used just over wood flour fire
Discharge (s)	50	80
Mounting bracket	Rubber padded wall bracket	Rubber padded wall bracket
Carton Size (mm)	200x155x590	240x193x565
Kitemark approval	N	N
CE marked	Y	Y
Marine approved	N	N
BAFE approved	N	N