


Wet Chemical

Wet Chemical (F-class) fire extinguishers are designed for use against A class fires and specifically for F class cooking oil and fat fires. The extinguishers come with a five year guarantee provided they are serviced and maintained annually by a competent person in accordance with BS5306 Pt3, using manufacturer's spare parts, and in line with the manufacturer's recommendations.

Foam fire extinguishers are suitable for Class A and B fires involving flammable liquids such as oils, spirits, greases, fats and certain plastics. The Wet Chemical extinguisher is safe for inadvertent use on electrical equipment up to 1,000v at a distance of 1 metre.

Class A: Carbonaceous material such as wood, paper and textile

Class F: Cooking oil and fats fires

	M6L
	
Model type	6ltr Wet Chemical Stored Pressure
Body material	Steel cylinder, plastic boot
Neck ring material	steel
Valve	Brass
Hose/Nozzle	Rubber hose with brass thread ring/ Multi purpose nozzle
Internal finish	Polyester powder coating
External finish	Polyester powder coating

	M6L
Charge (Ltr)	6
Extinguishant	Neufrol M
Fire rating	13A / 75F
Working pressure @ 20°C	15 bar
Test pressure	30 bar
Operating temperature	5°C to 60°C
Full weight (kg)	11.00kg
Empty weight (kg)	4
Overall width (mm)	225mm
Overall height (mm)	560mm
Cylinder diameter (mm)	150
Min. Discharge range (m)	2-4
Discharge (s)	33
Mounting bracket	Rubber padded wall bracket
Carton Size (mm)	200x155x590
Kitemark approval	Y
CE marked	Y
Marine approved	N
BAFE approved	Y